



Typical Zone Controller Configuration

PowerEdge R330 Rack Server	Dell	PER330	ea
Chassis with up to 8, 2.5" Hot Plug Hard Drives	Dell		incl
Intel® Xeon® E3-1240 v5 3.5GHz, 8M cache, 4C/8T, turbo (80W)	Dell		incl
Performance Optimized	Dell		incl
2133MT/s UDIMMs	Dell		incl
(2x) 4GB UDIMM, 2133MT/s, ECC	Dell		incl
No Operating System	Dell		incl
iDRAC8 Enterprise, integrated Dell Remote Access Controller, Enterprise	Dell		incl
RAID 0+RAID 0, H330/H730 for SAS/SATA	Dell		incl
PERC H730 Integrated RAID Controller, 1GB Cache, for Hot Plug Chassis	Dell		incl
(2x) 1.2TB 10K RPM SAS 12Gbps 2.5in Hot-plug Hard Drive	Dell		incl
(1x) 300GB 15K RPM SAS 12Gbps 2.5in Hot-plug Hard Drive	Dell		incl
On-Board LOM 1GBE Dual Port (BCM5720 GbE LOM)	Dell		incl
PCIe Riser,1FH,1LP w/Fan,R330	Dell		incl
Dual, Hot-plug, Redundant Power Supply, 350W	Dell		incl
(2x) C13 to C14, PDU-Style, 13 Amp, 2 meter Power Cord N.Am.	Dell		incl
ReadyRails™ Sliding Rails With Cable Management Arm	Dell		incl
Bezel	Dell		incl
DVD+/-RW, SATA, Internal for 8HD Chassis	Dell		incl
Electronic System Documentation and OpenManage DVD Kit for R320	Dell		incl
3Yr Basic Hardware Warranty Repair: 5x10 HW-Only, 5x10 NBD Onsite	Dell		incl



Typical ADEK configuration – (older system)

291-1A-B, 2U Rackmount Chassis for 6 slot backplane, Fan/filter, ATX with Dual USB on front 1-3.5", 1-5.25", +3.5" Internal, Black	ADE K	291-B	ea
AS-C74, 2nd generation Intel® Core™ i7/i5/i3 Pentium and Xeon Industrial Long Life Motherboard for LGA 1155	ADE K	AS-C74	inc I
Intel® Q67 Express Chipset	ADE K		inc I
2x Intel® 82574L Giga LAN	ADE K		inc I
4 x DDR3 1066/1333 DIMM up to 32GB	ADE K		inc I
12x USB, 6x COM, 4x SATA2, 2x SATA3 RAID 0,1,5,10, 1x PCIe x16 2.0, 1x PCIe x4, 5x PCI Slots	ADE K		inc I
Intel Core i5-2500K Sandy Bridge 3.3Ghz, LGA 1155, 95W, Quad-Core Processor, 32 mn, 6MB Cache, Intel HD Graphics 3000 Processor, 32 mn, 6MB Cache, Intel HD Graphics 3000	ADE K	CI5-2500K-1155	inc I
8 GB DDR3 1333MHz 240-Pin RAM	ADE K	DDR3-8GB-1333	inc I
DVD RW SATA	ADE K		inc I
OEM Software Bundle, Discount, USB Optical Mouse&KB	ADE K		inc I
Operating System - Linux SuSE / Equiv.	ADE K		inc I

Typical DVR Configuration



PowerEdge R530 Rack Server, No TPM	Dell	PER530	ea
3.5" Chassis with up to 8 Hot Plug Hard Drives	Dell		incl
(2x) Intel® Xeon® E5-2630 v3 2.4GHz,20M Cache,8.00GT/s QPI,Turbo,HT,8C/16T (85W) Max Mem 1866MHz	Dell		incl
Performance Optimized	Dell		incl
2133MT/s RDIMMs	Dell		incl
(8x) 16GB RDIMM, 2133MT/s, Dual Rank, x4 Data Width	Dell		incl
No Operating System	Dell		incl
RAID 5 for H330/H730/H730P (3-8 HDDs or SSDs)	Dell		incl
PERC H730 RAID Controller, 1GB NV Cache	Dell		incl
(4x) 4TB 7.2K RPM NLSAS 6Gbps 3.5in Hot-plug Hard Drive	Dell		incl
iDRAC8 Enterprise, integrated Dell Remote Access Controller, Enterprise	Dell		incl
On-Board Broadcom 5720 Quad Port 1Gb LOM	Dell		incl
PCIe Riser	Dell		incl
Dual, Hot-plug, Redundant Power Supply (1+1), 750W	Dell		incl
(2x) C13 to C14, PDU Style, 12 AMP, 6.5 Feet (2m), Power Cord	Dell		incl
ReadyRails™ Sliding Rails With Cable Management Arm	Dell		incl
Bezel	Dell		incl
DVD+/-RW, SATA, Internal for 8HD Chassis	Dell		incl
Electronic System Documentation and OpenManage DVD Kit for R520	Dell		incl
3 Year ProSupport 4HR 7x24 Onsite: Non Mission Critical	Dell		incl